

Form 51-102F3
Material Change Report

Item 1 Name and Address of Company

Arizona Mining Inc. (“**Arizona Mining**” or the “**Company**”)
Suite 555 – 999 Canada Place, Vancouver, BC V6C 3E1

Item 2 Date of Material Change

September 13, 2016

Item 3 News Release

A news release was disseminated on September 13, 2016 by Canada NewsWire (CNW Group).

Item 4 Summary of Material Change

Vancouver, B.C., September 13, 2016 – Arizona Mining Inc. (TSX: AZ) (“Arizona Mining” or the “Company”) announced the results of a further two (2) exploration drill holes from its current program targeting the expansion of the Taylor Zn-Pb-Ag sulfide deposit located on its 100% owned Hermosa Project in Santa Cruz County, Arizona. These and the other recently completed drill holes continue to expand the maiden resource announced on February 1, 2016 of 39.4 million inferred tonnes grading 11% zinc equivalent.

Item 5 Full Description of Material Change

Arizona Mining announced the results of a further two (2) exploration drill holes from its current program targeting the expansion of the Taylor Zn-Pb-Ag sulfide deposit located on its 100% owned Hermosa Project in Santa Cruz County, Arizona. These and the other recently completed drill holes continue to expand the maiden resource announced on February 1, 2016 of 39.4 million inferred tonnes grading 11% zinc equivalent.

HDS-354 is an exploration step out hole located approximately 1,300 feet northwest of the existing resource area. This drill hole is important in extending the mineralization as it matches up well with the mineralized intervals from HDS-344 (announced June 28, 2016). The drill hole encountered intense alteration and recrystallization of the carbonate host and five (5) distinct mineralized intervals including a 24.5 foot interval which assayed 23.1% zinc, 13.5% lead, 0.10% copper and 7.3 ounces per ton (“opt”) silver within a 49.5 foot thick broader zone of mineralization which assayed 13.6% zinc, 8.04% lead, 0.11% copper and 4.79 opt silver.

HDS-362 is an angle hole drilled southwest from the patented claim block to extend the mineralization beyond the current resource boundary to the southwest. The drill hole encountered 11 distinct mineralized intervals including a 171 foot intercept grading 4.97% zinc, 3.61% lead, 0.04% copper and 1.12 opt silver. Included in this intersection were two significant higher grade intervals including a 24.5 foot interval which assayed 11.63% zinc, 8.04% lead, 0.07% copper and 2.37 opt silver, and a 9.5 foot interval assaying 11.59% zinc, 9.28% lead, 0.07% copper and 2.88 opt silver.

Arizona Mining CEO Jim Gowans commented, “We continue to be excited about the expansion potential highlighted both to the northwest and southwest as confirmed by HDS-354 and HDS-362. We continue our drilling program to test the limits of the mineralization and based on our success to date, we are in the process of increasing the number of drill rigs on the property from the current 10 core rigs to 15.”

Table I. Assay summaries for HDS-354 & HDS-362

DH_ID		From (feet)	To (feet)	Interval (in feet)	From (meters)	To (meters)	Interval (meters)	Ag opt	Pb%	Zn%	Cu%	Ore Zone
HDS-354		985	1030	45	300.2	313.9	13.7	5.19	2.34	3.76	0.23	CRD
HDS-354	Including	990	1004	14	301.7	306.0	4.3	12.51	5.10	8.26	0.58	CRD
HDS-354		1310.5	1360	49.5	399.4	414.5	15.1	4.79	8.04	13.63	0.11	CRD
HDS-354	Including	1330	1354.5	24.5	405.4	412.8	7.5	7.32	13.51	23.13	0.10	CRD
HDS-354		1491.5	1496	4.5	454.6	456.0	1.4	7.06	10.80	17.35	0.06	CRD
HDS-354		3226	3231.5	5.5	983.2	984.9	1.7	18.23	4.78	3.79	0.36	CRD
HDS-354		3805.5	3951.5	146	1159.9	1204.4	44.5	1.93	1.74	0.96	0.08	CRD
HDS-354	Including	3890.5	3895	4.5	1185.8	1187.1	1.4	15.14	2.99	0.02	0.01	CRD
HDS-354	Including	3915.5	3929	13.5	1193.4	1197.5	4.1	2.93	6.19	2.44	0.02	CRD
HDS-362		1803	1878	75	549.5	572.4	22.9	2.23	6.30	4.10	0.07	CRD
HDS-362		1903	1927	24	580.0	587.3	7.3	2.78	8.42	11.57	0.29	CRD
HDS-362		1968	1987	19	599.8	605.6	5.8	1.32	4.17	5.60	0.04	CRD
HDS-362		2057.5	2068	10.5	627.1	630.3	3.2	0.97	2.76	2.97	0.01	CRD
HDS-362		2143	2170	27	653.2	661.4	8.2	1.17	1.05	0.69	0.18	CRD
HDS-362		2257	2265.5	8.5	687.9	690.5	2.6	1.05	2.89	3.10	0.09	CRD
HDS-362		2290.5	2461.5	171	698.1	750.2	52.1	1.12	3.61	4.97	0.04	CRD
HDS-362	Including	2290.5	2326.5	36	698.1	709.1	11.0	1.66	5.19	7.19	0.08	CRD
HDS-362	Including	2357	2381.5	24.5	718.4	725.8	7.5	2.37	8.04	11.63	0.07	CRD
HDS-362	Including	2416.5	2432	15.5	736.5	741.2	4.7	2.03	6.45	8.41	0.04	CRD
HDS-362	Including	2452	2461.5	9.5	747.3	750.2	2.9	2.88	9.28	11.59	0.07	CRD
HDS-362		2506.5	2513	6.5	763.9	765.9	2.0	1.62	5.11	4.55	0.17	CRD
HDS-362		2552	2606	54	777.8	794.3	16.5	0.84	2.58	1.97	0.01	CRD
HDS-362		3076	3109	33	937.5	947.6	10.1	4.56	10.92	0.90	0.05	CRD
HDS-362	Including	3079	3092	13	938.4	942.4	4.0	10.43	25.34	1.92	0.10	CRD
HDS-362		3146	3186.5	40.5	958.9	971.2	12.3	2.02	3.88	4.77	0.05	CRD
HDS-362	Including	3146	3161.5	15.5	958.9	963.6	4.7	4.58	8.78	10.25	0.11	CRD

(Drill intersections with combined Zinc and Lead of >9% are highlighted. Drill intervals are down the hole drill width but are considered to be within 5% of true width)

Qualified Person

The results of the Arizona Mining Inc. drilling results have been reviewed, verified and compiled by Donald R. Taylor, MSc., PG, Chief Operating Officer for Arizona Mining Inc., a qualified person as defined by National Instrument 43-101 (NI 43-101). Mr. Taylor has more than 25 years of mineral exploration and mining experience, and is a Registered Professional Geologist through the SME (registered member #4029597).

Assays and Quality Assurance/Quality Control

To ensure reliable sample results, the Company has a rigorous QA/QC program in place that monitors the chain-of-custody of samples and includes the insertion of blanks, duplicates, and certified reference standards at statistically derived intervals within each batch of samples. Core is photographed and split in half with one-half retained in a secured facility for verification purposes.

Sample preparation (crushing and pulverizing) has been performed at ALS Minerals Laboratories, an ISO/IEC accredited lab located in Tucson, Arizona. ALS Minerals Laboratories prepares a pulp of all samples and sends the pulps to their analytical laboratory in Vancouver, B.C. Canada for analysis. ALS analyzes the pulp sample by ICP following a 4-acid digestion (ME-ICP61 for 33 elements) including Cu (copper), Pb (lead), and Zn (zinc). All samples in which Cu (copper), Pb (lead), or Zn (zinc) are greater than 10,000 ppm are rerun using four acid digestion with an ICP – AES finish (Cu-OG62;Pb-OG62; and Zn-OG62) with the elements reported in percentage (%). Silver values are determined by ICP (ME-ICP61) with all samples with silver values greater than 100 ppm repeated using four acid digestion with an ICP-AES finish (Ag-OG62) calibrated for higher levels of silver contained. Any values over 1,500 ppm

Ag triggers a fire assay with gravimetric finish analysis. Gold values are determined by a 30 gm fire assay with an ICP-AES finish (Au-ICP21).

Item 6 Reliance on subsection 7.1(2) of National Instrument 51-102

This Report is not being filed on a confidential basis in reliance on subsection 7.1(2) of National Instrument 51-102.

Item 7 Omitted Information

None

Item 8 Executive Officers

Purni Parikh, Vice President & Corporate Secretary (604) 638-2003

Paul Ireland, Chief Financial Officer (604) 687-1717

Item 9 Date of Report

September 13, 2016