

WESCAN GOLDFIELDS INC.

FORM 51-102F3

MATERIAL CHANGE REPORT

1. Name and Address of Company

Wescan Goldfields Inc. (the "**Corporation**")
300, 224 – 4th Avenue S.
Saskatoon, Saskatchewan
S7K 5M5

2. Date of Material Change

June 24, 2005

3. News Release

On June 24, 2005, the Corporation issued a press release disclosing the nature and substance of the material change (**a copy of which is attached as Schedule "A" to this Material Change Report**).

4. Summary of Material Change

The Corporation has announced that Wescan Goldfields Inc. and Claude Resources Inc. have commenced drilling on the Jojay Gold deposit.

5. Full Description of Material Change

See the press release attached as Schedule "A" to this Material Change Report for a full description of the material change.

6. Reliance on subsection 7.1(2) or (3) of National Instrument 51-102

Not applicable.

7. Omitted Information

No material information has been omitted from this report.

8. Executive Officer

For further information, please contact Mr. George Sanders, President at (306) 664-2422.

9. Date of Report

DATED at Saskatoon, Saskatchewan this 24th day of June, 2005.

SCHEDULE "A"

**Stock Symbol: WGF: TSX-VEN
WESCAN GOLDFIELDS INC.**

**June 24, 2005
Saskatoon, Saskatchewan**

WESCAN AND CLAUDE COMMENCE DRILLING ON JOJAY GOLD DEPOSIT

George Sanders, President of Wescan Goldfields Inc. ("Wescan") is pleased to report that diamond drilling has commenced on the Jojay gold deposit. The Company holds a 25% joint venture interest with Claude Resources Inc. ("Claude") holding the balance. Wescan is the operator. The Jojay deposit is situated in the La Ronge – Lynn Lake Greenstone Belt in northern Saskatchewan.

Several phases of exploration drilling totalling over 12,000 metres have been conducted by previous operators including Claude, Cameco Corp. and its predecessor company S.M.D.C., and by Cominco Ltd. Gold mineralization typically occurs in shear zones situated near or at a sediment-volcanic lithological contact. Five separate gold zones have been identified by previous drilling and existing glacial till anomalies due south of the deposit indicate there may be other gold zones that have not yet been uncovered. Most of the zones remain open along strike and down plunge. As noted in a June 2003 project summary by independent geologic consultants A.C.A. Howe International Limited, a preliminary analysis in 1987 by Kilborn Engineering reports an inferred resource of 750,000 tons at a grade of 0.24 oz per ton. This resource was later refined to a National Policy 2A-compliant geological reserve of 313,000 tons at 0.264 oz per ton to 150 metre depth (cross-sectional polygonal method, 1.2 metre mining width, 0.10 oz/ton cut off). This historic data together with information from the current drill program will be reanalysed with a view to generating a NI43-101 compliant resource/reserve calculation.

The current program consists of six diamond drill holes totalling 1,270 metres. The program is designed to upgrade the confidence level of certain portions of the "Red Zone" (the most significant zone to date) and to test down plunge extensions. The drill holes are also designed to test the nature and extent of gold mineralization found in the vicinity of the Gnat Lake Fault.

Mr. Frank Hrды, P. Geo., Wescan's Exploration Manger is the Qualified Person in accordance with NI43-101 and has reviewed this news release.

Wescan is a Canadian based Company engaged in the acquisition, exploration and development of mineral properties. Shore Gold Inc. owns 22% of Wescan's fully diluted common shares.

For further information please contact:

George Sanders, President or Wade MacBain, Corporate Development at (306) 664-2422.

-END-

"The TSX Venture Exchange has not reviewed and does not accept responsibility for the adequacy or accuracy of this release."