

October 6, 2016
NEWS RELEASE - #16-14
TSX- V: GRR

Table 1. San Albino Gold Deposit – 2016 Grade Control Drill Results

Hole ID	From (m)	To (m)	Width (m)	Au (g/t)	Ag (g/t)
SA16-RC-01	16 including 1m @ 46.30 g/t Au and 91.3 g/t Ag; and including 1m @ 71.70 g/t Au and 93.2 g/t Ag including 1m @ 30.00 g/t Au and 38.5 g/t Ag	20	4	37.70	57.7
SA16-RC-02	0	1	1	2.75	4.8
SA16-RC-04	0	1	1	2.45	4.3
	18	19	1	6.96	4.3
SA16-RC-05	14 including 1m @ 25.90 g/t Au and 53.2 g/t Ag	19	5	6.87	15.7
SA16-RC-06	11 including 2m @ 25.95 g/t Au and 46.9 g/t Ag	14	3	17.85	36.2
SA16-RC-07	12 including 3m @ 35.60 g/t Au and 92.7 g/t Ag	16	4	27.10	74.6
SA16-RC-08	0	1	1	6.15	15.8
SA16-RC-09	0	1	1	1.12	5.1
	7	10	3	7.41	14.8
SA16-RC-10	4 including 2m @ 32.10 g/t Au and 54.3 g/t Ag	7	3	22.07	38.5
SA16-RC-11	0	2	2	3.17	7.3
SA16-RC-11	9 including 2m @ 35.40 g/t Au and 52.0 g/t Ag	13	4	19.19	30.9
SA16-RC-12	0	1	1	7.43	5.9
SA16-RC-15	0	1	1	1.33	3.0
SA16-RC-22	18 including 2m @ 10.06 g/t Au and 18.6 g/t Ag	21	3	7.06	15.4
SA16-RC-23	9 including 1m @ 33.20 g/t Au and 43.2 g/t Ag	11	2	21.38	34.0
SA16-RC-24	0	4	4	3.01	7.6
SA16-RC-24	8 including 2m @ 22.25 g/t Au and 51.0 g/t Ag	11	3	16.27	41.9
SA16-RC-25	0	1	1	7.33	8.6
	4	7	3	1.38	2.2
SA16-RC-26	0	1	1	1.09	2.9
	2	3	1	1.06	1.6
SA16-RC-27	0	2	2	1.09	2.1
SA16-RC-28	0	1	1	1.89	3.1

Hole ID	From (m)	To (m)	Width (m)	Au (g/t)	Ag (g/t)
SA16-RC-29	0	1	1	1.34	2.2
SA16-RC-31	4	6	2	1.90	1.4
SA16-RC-32	0	2	2	3.74	7.1
SA16-RC-34	1	5	4	4.45	7.7
SA16-RC-35	1	5	4	1.29	1.9
SA16-RC-36	3	7	4	4.72	3.6
SA16-RC-37	4	8	4	7.63	13.6
SA16-RC-38	4	7	3	1.71	2.2
SA16-RC-39	0	3	3	4.44	5.8
SA16-RC-40	0	1	1	28.40	6.1
SA16-RC-41	0	1	1	3.47	3.5
SA16-RC-42	0	6	6	4.47	6.9
	17	18	1	7.05	10.7
SA16-RC-43	1	3	2	15.24	20.3
SA16-RC-44	0	5	5	3.73	16.8
SA16-RC-47	0	1	1	10.90	24.6
SA16-RC-51	1	2	1	8.28	4.5
SA16-RC-55	8	10	2	2.74	6.6
SA16-RC-56	6	7	1	7.31	13.1
SA16-RC-58	16	17	1	28.70	49.3
SA16-RC-59	12	14	2	12.25	20.9
SA16-RC-60	10	12	2	16.10	33.9
SA16-RC-61	6	9	3	38.38	43.6
	including 2m @ 55.10 g/t Au and 59.7 g/t Ag				
SA16-RC-62	3	7	4	19.43	26.6
	including 2m @ 36.95 g/t Au and 49.1 g/t Ag				
SA16-RC-63	2	5	3	20.40	32.8
SA16-RC-64	0	2	2	4.31	5.3
SA16-RC-65	0	1	1	2.02	1.4
SA16-RC-66	2	4	2	4.32	18.4
SA16-RC-67	2	3	1	7.10	8.8
SA16-RC-68	0	8	8	4.58	18.5
	including 1m @22.70 g/t Au and 105.0 g/t Ag				
SA16-RC-69	11	12	1	8.24	18.8
SA16-RC-70	0	11	11	2.82	6.1
	17	18	1	1.13	1.1
SA16-RC-71	4	5	1	1.25	1.0
SA16-RC-72	1	2	1	1.90	0.8
SA16-RC-79	10	11	1	1.39	2.5
SA16-RC-80	9	10	1	1.10	2.4

Hole ID	From (m)	To (m)	Width (m)	Au (g/t)	Ag (g/t)
SA16-RC-81	2	3	1	1.11	4.3
SA16-RC-82	4	6	2	2.23	4.6
SA16-RC-84	2	3	1	1.33	1.8
SA16-RC-86	1	2	1	1.08	3.0

The above table represents an average of uncapped composite intervals intercepted by close space Reverse Circulation grade-control drilling. The Company has utilized a cut-off grade of 1.0 g/t Au over a length of 1 metre, which has reduced the length of certain reported mineralized intersections.