



AMITY OIL LIMITED

A.C.N. 009 230 835

Our Ref: 2003 09 04ASXS7016HM A2:AO126:WR

4th September 2003

Manager
Companies Announcements Office
Australian Stock Exchange Ltd
10th Floor, 20 Bond Street
SYDNEY NSW 2000

Dear Madam,

Adatepe-2 Well, 4th September 2003

Main Points

Drilling ahead at 1077 metres.

Operations Summary for 24 Hours to 0400 Hours 4th September 2003

Drill ahead at 9 metres/hour to 1049 metres. Ran survey, 1.5 degree off vertical. Drilled to 1077 metres. Mud weight 9.7 ppg.

Geological Summary

Lithology dominated by claystones and marls and minor sands. Trip gas 2%.

Operations in the Next 24 Hours

Drill ahead.

Well Location

The Adatepe-2 well is a development well on the Adatepe Field located approximately 6 kilometres southeast of the Gocerler Gas Field. It is positioned 438 metres southeast of Adatepe-1 well at Latitude 41 19 00.074 N and Longitude 27 49 59.225 E.

The well will be drilled in Petroleum Exploration Licence AR/AOI/3648, which forms part of "Area A" of the Thrace Joint Venture and is located approximately 120 kilometres west of Istanbul in Turkey's onshore Thrace Basin.

Drilling Target

The Adatepe structure is a faulted anticlinal closure located on a northwest-southeast trending fault bound horst in an area coincident with strong amplitudes on the 3D seismic data. The closest wells to Adatepe-2 are Adatepe-1, Gocerler-3, 4 and 5 and Bahcedere-1. Gocerler-3 was drilled in March 2002 and achieved a record gas flow for Turkey (32 mmcfd). Adatepe-2 will test the hydrocarbon and reservoir potential of the Danisman sands to appraise the production potential and extent of the Adatepe Field. Adatepe-2 will be drilled to 1275 metres into the varved shale where the Danisman Formation reservoirs will be evaluated. The well is interpreted to have the same structure elevation as Adatepe-1 at the key gas sand horizon.

Amity Oil Limited

Level 2, 18 Richardson Street West Perth WA 6005
PO Box 690 West Perth WA 6872

Telephone: (08) 9324 2177 Facsimile: (08) 9324 1224 Email: mail@amityoil.com.au Website: www.amityoil.com.au

Drilling Program

The well will be drilled with a modified KCL-Polymer mud to avoid the high level of reservoir damage in the Danisman section, commonly associated with conventional overbalanced drilling of these sensitive sandstone reservoir units. Formation damage arises from the presence of water sensitive interstitial clays particularly within the Danisman reservoir sandstones. Hydrocarbons exist in the upper portion of the Danisman Formation. Based on results of Adatepe-1, the shallowest of these potential secondary targets is at 868 metres. Surface casing will be set into the top of the Danisman Formation and the BOPs connected for well control, prior to drilling into the gas bearing section of the Danisman Formation.


Ownership

Participants in the well are:

Amity Oil International Pty Ltd	50% (operator),
Türkiye Petrolleri A.O.	50%

For more information and images, please refer to Amity's website at www.amityoil.com.au.

Yours faithfully,
AMITY OIL LIMITED



HOWARD McLAUGHLIN
Managing Director